

# SUBMITTAL



## RieberLok™ Gasket for Internal Restraint of AWWA C900 PVC Pipe & Fittings Originally Fitted with a Rieber Gasket



### SUBMITTAL INFORMATION

PROJECT NAME:

ENGINEER:

CONTRACTOR:

SPEC. SECTION:

DATE:

### Information:

- FM Approved
- Available in SBR or EPDM
- Stainless steel locking segments unaffected by corrosive elements
- Can be Pre-installed at the plant or field installed
- Works on all C900 pipe & PVC pressure fittings that originally use a Rieber gasket
- Rated at the pipe or PVC pressure fitting rating with a 2:1 safety factor
- Allows the full deflection of the joint, as recommended by the pipe or fitting manufacturer
- Suitable for open trench, road bores, and casing applications. Please contact RieberLok for HDD applications
- Size range of 4" - 16" for C900 CIOD & 3" - 8" C900 IPS
- Works on C900 DR14, DR18, and DR25 for C900 CIOD & SDR17, SDR21, & SDR26
- Assembly instructions, field cut instructions, and FAQs on [www.RieberLok.com](http://www.RieberLok.com)

### Gasket Material Options:

SBR

EPDM



Registered Trademark of Ransom International, LLC.  
Ransom International, LLC.  
David Martin (205)-397-9464  
[www.RieberLok.com](http://www.RieberLok.com)